Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

- 1. (canceled)
- 2. (previously amended) The method of claim 3 wherein power output from the starter motor is regulated to meet existing and impending power demands by drive system auxiliary devices.
- 3. (previously amended) A method for reducing exhaust emissions during cold start of an internal combustion engine, the engine being coupled to a starter motor and an exhaust gas treatment device, comprising:

providing assist to the engine by the starter motor to meet a demanded power when a temperature of the exhaust gas treatment system is less than an operating temperature of the exhaust gas treatment device; and

operating the starter motor as a generator after the operating temperature of the exhaust gas treatment device has been reached.

4. (currently amended) A method for reducing exhaust emissions during cold start of an internal combustion engine, the engine being coupled to a starter motor and an exhaust gas treatment device, comprising:

providing assist to the engine by the starter motor to meet a demanded power until a temperature of the exhaust gas treatment system reaches an operating temperature of the exhaust gas treatment device; and The method of claim 6, further comprising: retarding spark timing of the engine.

prising:

6-7. (canceled)

- 8. (previously amended) The method of claim 10, further comprising: retarding spark timing of the engine.
- 9. (previously amended) The method of claim 10, further comprising: heating the exhaust gas treatment device by electric heater coupled to the exhaust gas treatment device.
- 10. (currently amended) The method of claim 46, further comprising: delaying a shifting operation of an automatic transmission coupled to the internal combustion engine.

11. (canceled)

- 12. (currently amended) The system of claim 164 wherein said electronic control unit causes spark timing of the engine to be retarded.
- 13. (currently amended) The system of claim 164 wherein said electronic control unit causes an electric heater coupled to the exhaust gas treatment device to heating the exhaust gas treatment device.

14-15. (canceled)

16. (currently amended) An engine system comprising:
an internal combustion engine:
a starter motor coupled to said engine;

<u>an exhaust gas trea</u>	tment device arranged in an engine exhaust of
a control unit electronical	ly coupled to said engine and said starter motor
said control unit causing said sta	rter motor to provide need said starter motor

a control unit electronically coupled to said engine and said starter motor said control unit causing said starter motor to provide power to reduce a power provided by said engine until said exhaust gas treatment device achieves an operating temperature. The system of claim 14 wherein said electronic control unit causes spark timing of the engine to be retarded.

17. (currently amended) The system of claim 164 wherein said electronic control unit causes an electric heater coupled to the exhaust gas treatment device to heating the exhaust gas treatment device.

18. (canceled)

- 19. (currently added) The engine system of claim 164 wherein said starter motor is an integrated starter generator.
- 20. (currently amended) The method of claim 46, further comprising: discontinuing providing assist by the starter motor when a temperature of the exhaust treatment device exceeds said operating temperature.
- 21. (currently amended) The method of claim 46 wherein said operating temperature is a temperature at which the exhaust treatment device becomes active.
- 22. (currently a amended) The method of claim 46 wherein said starter motor is an integrated starter generator.
- 23. (currently amended) The method of claim 22, further comprising: operating said integrated starter generator as a generator when a temperature of the exhaust treatment device exceeds said operating temperature.

24. (canceled)

- 25. (currently amended) The method of claim 274 wherein said enginesupplies a lesser amount of power than otherwise because of power supplied by the starter motor when both the engine and starter motor are operating.
- 26. (currently amended) The method of claim 274 wherein said operating both the engine and the starter motor has both the engine and the starter motor providing mechanical power.
- 27. (currently amended) A method for reducing exhaust emissions during cold start of an internal combustion engine, the engine being coupled to a starter motor and an exhaust gas treatment device, comprising:
 - supplying rotational energy to the engine at rest by the starter motor;
 - providing fuel to the engine when an engine rotational speed substantially exceeds an idle speed;
 - continuing to operate both the engine and the starter motor after fuel is provided to the engine until the exhaust gas treatment device reaches a predetermined temperature; and

The method of claim 24, further comprising: discontinuing operation of the starter motor when a temperature of the exhaust treatment device exceeds said predetermined temperature.

- 28. (previously amended) The method of claim 27 wherein said predetermined temperature is a temperature at which the exhaust treatment device becomes active.
- 29. (currently amended) The method of claim 3024 wherein said starter motor is an integrated starter generator.

	30. (currently amended) A method for reducing exhaust emissions during co
	start of an internal combustion engine, the engine being coupled to a starte
	motor and an exhaust gas treatment device, comprising:
	supplying rotational energy to the engine at rest by the starte
	providing fuel to the engine when an engine rotational speed substantially exceeds an idle speed;
	continuing to operate both the engine and the starter make
	Act is provided to the engine until the exhaust gas treatment desired
	reduced the second seco
	The method of claim 29, further comprising: operating said integrated
	and temperature of the same and the same of the same o
1	treatment device exceeds said predetermined temperature.

31. (previously amended) The method of claim 27 wherein when the

starter motor operation is discontinued, the starter motor provides substantially

no positive or negative torque.